

Flamex B-F Black

PU Film Hose, lightweight, highly flexible and compressible



Material

spiral: spring steel wire
wall: polyester polyurethane
wall thickness between spirals approx. 0.5 mm

Applications

- Extraction of oil mist
- Dust, fumes and powder applications in a wide range of industries

Properties

- extremely flexible
- lightweight
- smallest bending radii
- abrasion resistant
- oil resistant

Temperature Range

- -40°C to +90°C
- peaks to +125°C

Flamex B-F Black

DN	op pressure c. bar	vacuum c. mmWG	bending radius c. mm	outer Ø c. mm	weight c. kg/m	article no.	stock length
75	0.61	1300	43	83	0.52	310BK-075-1000	10m
100	0.46	900	55	108	0.69	310BK-100-1000	10m
125	0.38	900	68	136	0.85	310BK-125-1000	10m
150	0.30	600	80	159	1.02	310BK-150-1000	10m
160	0.30	600	85	169	1.08	310BK-160-1000	/
200	0.23	600	105	210	1.26	310BK-200-1000	10m


All data refers to a media and ambient temperature of +20 °C

* refers to the inside of the hose

Manufactured to order, lead time approx' 7days

Available on request in other lengths and sizes .

Subject to technical changes and colour deviations.




Hose Reducer,
symmetrical



Master-Grip Hose Clamp,
screwable



Master-Grip Quick-Fix
Clamp



Hose Connector