

Streetmaster GKS

PU Large Street-Cleaner Suction Hose, highly abrasion / vacuum / microbe-resistant

Material

- 1 spiral: spring steel wire
- 2 wall: pure polyether polyurethane, microbe resistant
- 3 wall thickness between spirals approx. 1.8 - 3.4 mm

Applications


- suction & transport hose for abrasive solids, for which microbe and hydrolisis resistance is required
- granulate transport hose
- standard hose for industrial vacuum cleaners
- transport of chips/shavings
- oil mist extraction/suction
- suction and transport of paper fibres

Properties

- municipal and waste disposal vehicles
- suction dredger hose
- suction hose for larger sweepers
- suction & transport hose for abrasive solids, which require microbe resistance


Temperature Range

- -40°C to +90°C
- peaks to +125°C



DN	op. pressure	vacuum	bend radius	outer Ø	weight/m	old article no.	new article no.	standard length	max. production length
mm	bar	bar	mm	mm	kg			m	m
225	0.6	0.36	525	240	4.7	130-225-x	000217-225-x	10	20
250	0.6	0.32	585	269	5.4	130-250-x	000217-250-x	10	20
280*	0.5	0.28	655	295	6.3	130-280-x	000217-280-x	10	20

All data refers to a medium and ambient temperature of +20 °C.
 * Available on request
 Subject to technical changes and colour deviations.



Combiflex PU fixed flange



Hose Clamp with Bolts



PU Cuff, pre-fitted